

RECOMMENDED CUTTING CONDITIONS

Shoulder milling

Work material	Carbon steel, Cast iron, Alloy steel (-30HRC)			Alloy steel, Tool steel, Pre-hardened steel			Austenitic stainless steel, Titanium alloy		
	AISI 1050, AISI 35, AISI P20 etc.			AISI H13, AISI W1-10, AISI P21 etc.			AISI 304, AISI 306, Ti-6Al-4V etc.		
DC (inch)	Revolution	Table feed		Revolution	Table feed		Revolution	Table feed	
	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)
.0625	13000	550	21.7	8500	310	12.2	7100	200	7.9
.1250	8000	770	30.3	5100	380	15.0	4200	220	8.7
.1875	6300	880	34.6	3800	490	19.3	3200	250	9.8
.2500	5000	950	37.4	3000	500	19.7	2500	270	10.6
.3125	4000	1000	39.4	2400	560	22.0	2000	280	11.0
.3750	3300	1000	39.4	2000	490	19.3	1700	290	11.4
.4375	2900	970	38.2	1700	450	17.7	1400	300	11.8
.5000	2500	860	33.9	1500	420	16.5	1300	300	11.8
.5625	2200	790	31.1	1300	370	14.6	1100	280	11.0
.6250	2000	720	28.3	1200	350	13.8	1000	260	10.2
.7500	1700	610	24.0	1000	290	11.4	800	240	9.4

Depth of cut

$\leq 0.2DC$ ($DC > \phi.1094$)
 $\leq 0.1DC$ ($DC \leq \phi.1250$)

Drilling

Work material	Carbon steel, Cast iron, Alloy steel (-30HRC)			Alloy steel, Tool steel, Pre-hardened steel			Austenitic stainless steel, Titanium alloy		
	AISI 1050, AISI 35, AISI P20 etc.			AISI H13, AISI W1-10, AISI P21 etc.			AISI 304, AISI 306, Ti-6Al-4V etc.		
DC (inch)	Revolution	Table feed		Revolution	Table feed		Revolution	Table feed	
	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)
.0625	11000	120	4.7	7600	80	3.1	6000	20	0.8
.1250	8000	260	10.2	5000	180	7.1	4000	50	2.0
.1875	6300	300	11.8	3800	210	8.3	2700	60	2.4
.2500	5000	310	12.2	3000	210	8.3	2000	70	2.8
.3125	4000	320	12.6	2400	220	8.7	1600	80	3.1
.3750	3300	330	13.0	2000	240	9.4	1300	70	2.8
.4375	2900	330	13.0	1700	220	8.7	1100	70	2.8
.5000	2500	310	12.2	1500	210	8.3	1000	70	2.8
.5625	2200	270	10.6	1300	180	7.1	900	60	2.4
.6250	2000	250	9.8	1200	180	7.1	800	55	2.2
.7500	1700	200	7.9	1000	140	5.5	700	55	2.2

Depth of cut

$\le 1DC$ ($DC \ge \phi.0781$)
 $\le 0.5DC$ ($DC < \phi.0938$)

Slotting

Work material	Carbon steel, Cast iron, Alloy steel (-30HRC)			Alloy steel, Tool steel, Pre-hardened steel			Austenitic stainless steel, Titanium alloy		
	AISI 1050, AISI 35, AISI P20 etc.			AISI H13, AISI W1-10, AISI P21 etc.			AISI 304, AISI 306, Ti-6Al-4V etc.		
DC (inch)	Revolution	Table feed		Revolution	Table feed		Revolution	Table feed	
	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)	(min ⁻¹)	(mm/min)	(IPM)
.0625	11000	230	9.1	7600	150	5.9	6000	60	2.4
.1250	8000	600	23.6	5000	320	12.6	4000	130	5.1
.1875	6300	660	26.0	3800	360	14.2	2700	140	5.5
.2500	5000	720	28.3	3000	390	15.4	2000	140	5.5
.3125	4000	780	30.7	2400	430	16.9	1600	140	5.5
.3750	3300	740	29.1	2000	380	15.0	1300	150	5.9
.4375	2900	730	28.7	1700	340	13.4	1100	150	5.9
.5000	2500	700	27.6	1500	330	13.0	1000	140	5.5
.5625	2200	630	24.8	1300	300	11.8	900	140	5.5
.6250	2000	600	23.6	1200	290	11.4	800	130	5.1
.7500	1700	510	20.1	1000	240	9.4	700	120	4.7

Depth of cut

$\le 1DC$ ($DC \ge \phi.0781$)
 $\le 0.5DC$ ($DC < \phi.0938$)

- 1) When cutting austenitic stainless steels, the use of water-soluble cutting fluid is especially effective.
- 2) If the depth of cut is smaller than this table, feed rate can be increased.
- 3) If the rigidity of the machine or the workpiece installation is very low, or chattering is generated, please reduce the revolution and the feed rate proportionately.